

IEEE Searches:

LDAP - 11 hits

ldap and transaction - 2 hits

Google.com Searches:

ldap transaction

ProQuest Searches:

ldap and transaction - 95 hits

ldap and transaction w/2 (id or identifier)

ldap and (session or transaction) w/2 (id or identifier)

ldap and (transaction) and (commit or rollback)

Edelman, Bradley

Google.com Search:

Idap transaction

Idap transaction commit

Idap transaction commit modify delete add

	L #	Hits	Search Text	DBs
1	L1	218	((transaction or session) near3 (id or ticket or token or identifier)) with (server near4 (assign\$3 or creat\$3))	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
2	L2	205	(client near3 request\$3) with (start\$3 or new) near3 (session or transaction)	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
3	L3	65	transaction near3 (id or identifier) with (add\$3 or delet\$3 or modify or modifying) with (database or record)	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
4	L4	17	1 and 2	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
5	L5	7	4 and (@ad<20000330 or @prad<20000330)	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
6	L6	28	3 and (@ad<20000330 or @prad<20000330)	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
7	L7	1187	transaction near3 control and transaction near3 (id or identifier)	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
8	L8	460	transaction near3 control with (new or start or open or close)	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
9	L9	106	7 and 8	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
10	L10	76	9 and (@ad<20000330 or @prad<20000330)	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
11	L11	55	10 and database	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
12	L12	126	transaction near3 control with (commit or rollback or roll\$3 adj back)	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
13	L13	67	12 and transaction near3 (id or identifier)	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
14	L15	46	14 and database	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
15	L14	49	13 and (@ad<20000330 or @prad<20000330)	USPAT; US-PGPUB; EPO; JPO; IBM_TDB

	L #	Hits	Search Text	DBs
1	L1	1034	ldap and transaction and client and server	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
2	L2	129	ldap and transaction near3 (id or identifier) and client and server	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
3	L3	73	ldap and transaction near3 (id or identifier) same (client or server)	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
4	L4	18	3 and (@ad<20000330 or @prad<20000330)	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
5	L5	120	ldap and transaction adj2 (id or identifier)	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
6	L6	4	txnid	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
7	L7	55	5 and (@ad<20000330 or @prad<20000330)	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
8	L8	10	ldap adj v3	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
9	L9	903	(assign\$3 or generat\$4) near5 (transaction adj2 (identifier or id) or xid or tid)	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
10	L10	204	9 and client near5 request\$3	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
11	L11	140	9 with server	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
12	L12	82	10 and 11	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
13	L14	0	13 and ldap	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
14	L13	31	12 and (@ad<20000330 or @prad<20000330)	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
15	L15	544	(transaction adj (id or identifier)).clm,ti,ab.	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
16	L16	1	15 and commit and ldap	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
17	L17	160	15 and (request\$3) near5 (host or client or server)	USPAT; US-PGPUB; EPO; JPO; IBM_TDB

	L #	Hits	Search Text	DBs
18	L18	59	17 and (@ad<20000330 or @prad<20000330)	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
19	L19	1041	((transaction or session) adj (id or identifier)).clm,ti,ab.	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
20	L20	458	19 and (request\$3) near5 (host or client or server)	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
21	L21	241	20 and (new or commit or rollback or modify or delete or add) near6 (request\$4 or transaction)	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
22	L23	86	21 and (@ad<20000330 or @prad<20000330)	USPAT; US-PGPUB; EPO; JPO; IBM_TDB
23	L24	1	6011794.pn.	USPAT; US-PGPUB; EPO; JPO; IBM_TDB